

KEY FEATURES

Signalling

- Private Line™
- 5-tone selective signalling

Adaptable and versatile

- Option board capable
- Easily programmed in the field to support additional features

Easy to use and set-up

- Programmable buttons for easy access to frequently used features
- Ruggedised design and compelling user interface
- Simple menus and alpha-numeric phonebook

Protecting users

- Emergency signalling
- Lone worker feature for staff working remotely
- Whisper mode for discreet communications
- Caller identification

Quality

- MIL Spec 810 compliant
- Meets IP54 environmental standards
- Passed Motorola Accelerated Life Test
- X-Pand™ voice compression technology

Efficiency

- Channel scanning
- Call management features include call forwarding, escalating incoming call alert and missed calls list

Included as standard

- Battery
- Antenna
- Belt clip
- Accessory dust cover
- User manual

Accessory options

A wide range of accessory options are available to customise your radio

- Audio accessories
- Batteries and chargers
- Carry options

For full details of available accessories, please contact your local dealer or distributor



GP360

Efficiency Through Communication.

The GP360, one of the market-leading radios in Motorola's Professional Series, is an effective communication solution for larger organisations with many teams. The radio offers broad functionality; an easy-to-use menu with navigation keys for productivity, whilst security features protect users working alone or remotely.

With option board capability and a wide range of accessories available within the Professional Series; it's easy to build a tailored communications solution to meet your needs.

SPECIFICATIONS

GENERAL SPECIFICATIONS			
Channel Capacity		255	
Power Supply		Rechargeable battery 7.5v	
Dimensions: H x W x D (mm)		Height excluding knobs	
With Standard high capacity NiMH battery		137 x 57.5 x 37.5	
With Ultra high capacity NiMH battery		137 x 57.5 x 40.0	
With NiCD		137 x 57.5 x 40.0	
With Li-Ion battery		137 x 57.5 x 33.0	
Weight: (gm)			
With Standard high capacity NiMH battery		428	
With Ultra high capacity NiMH battery		508	
With NiCD battery		458	
With Li-Ion battery		358	
Average battery Life @5/5/90 Cycle:		Low Power	High Power
With Standard high capacity NiMH battery		11 hours	8 hours
With Ultra high capacity NiMH battery		14 hours	11 hours
With NiCD battery		12 hours	9 hours
With Li-Ion		11 hours	8 hours
Sealing:		Withstands rain testing per MIL STD 810 C/D/E and IP54	
Shock and Vibration:		Protection provided via impact resistant housing exceeding MIL STD 810-C/D/E and TIA/EIA 603	
Dust and Humidity:		Protection provided via environment resistant housing exceeding MIL STD 810 C/D/E and TIA/EIA 603	
Operating temperature:		-20°C to +55°C	

PORTABLE MILITARY STANDARDS 810 C, D & E						
Applicable MIL-STD	810C		810D		810E	
	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2
High Temperature	501.1	1,2	501.2	1,2	501.3	1,2
Low Temperature	502.1	1	502.2	1,2	502.3	1,2
Temp. Shock	503.1	1	503.2	1	503.3	1
Solar Radiation	505.1	1	505.2	1	505.3	1
Rain	506.1	1,2	506.2	1,2	506.3	1,2
Humidity	507.1	2	507.2	2,3	507.3	2,3
Salt Fog	509.1	1	509.2	1	509.3	1
Dust	510.1	1	510.2	1	510.3	1
Vibration	514.2	8,10	514.3	1	514.4	1
Shock	516.2	1,2,5	516.3	1,4	516.4	1,4

Data for +25°C unless otherwise specified

TRANSMITTER	
*Frequencies - Full Bandsplit	VHF: 136-174 MHz UHF: 403-470 MHz
Channel Spacing	12.5/20/25 kHz
Frequency Stability (-25°C to +55°C, + 25°C Ref.)	±2.5 ppm
Power	136-174: 1-5W 403-470: 1-4W
Modulation Limiting	±2.5 @ 12.5 kHz ±4.0 @ 20kHz ±5.0 @ 25 kHz
FM Hum & Noise	-40 dB typical
Conducted/Radiated Emission	-36 dBm <1 GHz -30 dBm >1 GHz
Adjacent Channel Power	-60 dB @ 12.6 kHz -70 dB @ 20/25 kHz
Audio Response (300-3000Hz)	+1 to -3dB
Audio Distortion	3%

RECIEVER	
*Frequencies - Full Bandsplit	VHF: 136-174 MHz UHF: 403-470 MHz
Channel Spacing	12.5/20/25 kHz
Frequency Stability (-25°C to +55°C, + 25°C Ref.)	±2.5 ppm
Sensitivity (12 dB SINAD) EIA	.25 µV typical
Sensitivity (20 dB SINAD) EN	.50 µV typical
Intermodulation EIA	70 dB
Adjacent Channel Selectivity	60 dB @ 12.5 kHz 70 dB @ 20/25 kHz
Spurious Rejection	70 dB
Rated Audio	0.5W
Audio Distortion	
@ Rated Audio	3% typical
Hum & Noise	-40 dB @ 12.5 kHz -50 dB @ 20/25 kHz
Audio Response (300-3000 Hz)	+ 1 to -3 dB
Conducted Spurious Emission	-57 dBm <1 GHz -47 dBm >1 GHz EN 300 086

*Availability subject to individual country's law and regulations.
Specifications are subject to change without notice and are issued for guidance only.
All specifications listed are typical. Radios meet applicable regulatory requirements.
Conforms to EC directive 89/336/EEC
Complies with EN 300 113
Contact your local Motorola Authorised Dealer to find out more about how communicating with the Professional Radio series will benefit your organisation.



Motorola Limited, EMEA Headquarters
Jays Close, Viabes Industrial Estate, Basingstoke, RG22 4PD, UK
Telephone: +44 (0)1256 358211
www.motorola.com

MOTOROLA and the Stylised M Logo are registered in the US Patent & Trademark Office.
All other product or service names are the property of their respective owners.
© Motorola, Inc. 2006. All rights reserved.
GP360-RE(08/06)